

AQUATECT S

A formulated blend of refined bitumens, mineral fibres, asphaltic gums, solvents and moisture inhibiting non-drying oils, that forms a seamless, high build coating with tremendous long lasting qualities.

Thixotropic outer surface protection for damp or dry application. Ideal for weather protection on all surfaces. One or two coats easy applied long term coating. Can be used with scrim to cover small cracks and joints.

APPLICATION

By soft brush, roller or airless spray. Ensure surface is free of grease, oil, mould growth etc.

FUNGICIDAL WASH should be used to remove algae, all loose surfaces should be made sound before applications.

On loose or bubbled felt cut affected area with a sharp instrument and seal down flat using the AQUATECT.

Pour AQUATECT onto surface and spread evenly with a large brush.

Where surface conditions are poor or extra protection is required a scrim should be pressed firmly into the first coat followed by a second coat the next day, the high build of 2 reinforced coats gives long service protection. (If area treated has to stand pedestrian traffic, dust with coarse sand while the coat is still tacky.)

AQUATECT over felt avoids the necessity of re-felting.

AQUATECT is a marvellous anti-corrosion coating for TANKS, PIPES and all METAL SURFACES.

Coverage – 350 – 500 sq ft per 25 kilo dependent upon substrate
Excellent Shelf Life.

Packed in 5 and 22.5 kilo containers.

STIR WELL BEFORE USE.

If proper preparation is carried out AQUATECT has a life expectancy of 10 years or more.

Do not add solvents to aid application or thinning for spraying.

It is advisable to wear protective clothing, gloves etc.

Keep away from naked flames, and use in a well ventilated area.

SURFACES

- LEAD
- ASBESTOS
- FELT
- ZINC

USES:

ALL ROOF SURFACES

- IRON
- VEHICLE ROOF
- CEMENT
- CARAVANS
- ZINC
- TILES
- LEAD



Equine • Agricultural • Gym • Play

WWW.QUATTRO.ORG.UK

ALUTECT

Alutect is a aluminium version of Aquatect S for the provision of excellent solar reflection.

As Alutect has the same thickness & same capabilities as Aquatect S it can be used as the second coat in its own right.

Alutect has a very long shelf life & is watertight immediately after application.

Specific Gravity	1.1 Kilos per Kg.
Film Build	0.5mm at 2 sq mtr per kilo (Smooth Surface).
Drying Time	1 to 2 hours.
Temp. Range	AQUATECT will not embrittle or flow between -25 Deg C to + 60 Deg C. Flashpoint : 60 Deg C +
Container sizes	5 and 22.5 kilos
Storage	AQUATECT will keep indefinitely in sealed containers. Store in a cool dry place



BEFORE



AFTER

AQUAFILL

Thixotropic towelling compound, easily seals cracks and joints. Applied in all weathers and to most surfaces. Aquafill is excellent for a quick repair or a permanent filler/sealer over holes or porous surface.

Prepare area to be treated, clean off loose particles, dust, algae & rust. Dry off as much as possible.

Apply direct from drum and trowel into split, crack or joint that needs sealing. Do not over trowel, if AQUAFILL sticks to trowel wipe with Solve this will aid application.

Available in 5kg units

Long shelf life

Equine • Agricultural • Gym • Play

WWW.QUATTRO.ORG.UK