

# Aquatank

# QUATTRO®

## The Rubber & Resin Specialists

Aquatank Bituminous Black Paint is a solvent-borne protective coating for use externally over ferrous and non-ferrous metals, concrete, roofing felt, fibre cement, corrugated iron, asphalt and wood.

Typical applications of Aquatank Bituminous Black Paint include asphalt and concrete roofs, non-potable water tanks, walls and corrugated iron sheeting.

Colour	Black upon application, drying to black.
Specific Gravity	0.9 approx.
Form	Low Viscosity
Composition	A bitumen solution
Application Temperature	+5°C to + 35°C

Coverage	4 to 6m <sup>2</sup> per lt depending on porosity of substrate
Drying Times	Touch dry in approx. 6 hours Fully dry in approx. 24 hours
Size Units	5 & 25 litres
Application	Brush on

### **Storage/Shelf Life**

Store and transport this container in a secure upright position. Ensure the lid is secure. Store for up to 24 months from date of manufacture in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +35°C and out of direct sunlight

### **PREPARATIONS**

1. Ensure the roof surface is structurally sound, clean, dry and free from oil, dirt, grease and loose material.
2. Remove any organic growth i.e. moss or lichen with Fungicidal Wash.
3. Metal surfaces should be wire brushed to remove rust. Any residual rust should be primed with Bitumen Penetration Primer for Roofs and allowed to dry for 24 hours.
4. Surfaces to be treated must be completely free of water.

### **APPLICATION**

5. Aquatank Bituminous Black Paint is ready for use and thinning is not normally necessary. Apply at least two coats by brush allowing each coat to dry (normally 24 hours) before applying the next.

### **Non-potable water tanks:**

6. Apply a minimum of two coats allowing at least 24 hours for drying between each coat. This may be longer depending on conditions. Thoroughly wash out the tank after the final coat has dried.

### **CLEANING**

7. Clean tools and equipment immediately after use with a proprietary brush cleanser. 8. Hardened material may be removed by soaking in cleanser. 9. Wash hands with a suitable resin dissolving hand cleanser.

PRECAUTIONS IN USE: Do not use internally. Do not apply to ponds, fishponds or swimming ponds. Do not apply when the surface is too hot. It is not advisable to work in humid or foggy weather conditions or when there is a risk of rain before the paint has dried.

**Equestrian • Agricultural • Gym • Play**

Quattro Products Limited, Milestone House Ind Est, Penrith, Cumbria, CA11 9NQ

Tel: 01768864977 Email: enq@quattro.org.uk Web: www.quattro.org.uk

